

UEI LPKITPLUS

TEST INSTRUMENTS™ LP PRO+ KIT

THE COMPLETE LP DIAGNOSTICS KIT

■ **CD100A Combustible Gas Leak Detector**

- Minimum detection 50 ppm methane
- 18" gooseneck
- 'Tip-light' in sensor cap
- Audio and visual tic rate
- Headphone jack

■ **C071A Carbon Monoxide Detector**

- Long life CO sensor
- Preset alarms
 - 3-color warning light
 - Audible alert
- MAX capture
- Low battery indicator
- CO detection to 999 ppm
- Backlit display
- One button auto zero

■ **EM151 Electronic Manometer**

- Single input to measure positive and negative pressure to 20" wg
- Measures in inches water gauge

■ **AC504 Hard Carrying Case**



LPKITPLUS • LP PRO+ KIT

The LPKITPLUS is the complete tank to inside appliance test kit for installers and service technicians. Check primary/secondary gas pressure verify fittings are leak free and test for CO levels in the living space.

CD100A Specifications

Sensitivity	50 ppm
Tic adjustment	Fully adjustable thumbwheel
Tic indication	Flashing LED
Battery	9 volt alkaline, 5 hours typical use
Sensor	Solid state semiconductor
Dimensions	8" x 4" x 1-1/2"
Weight	15 oz.

C071A Specifications

Range:		0 - 999 ppm
Resolution:		1 ppm
Accuracy:		±(3% of reading + 1 ppm)
Visual:		LCD and LED
Alarms	Visual:	Green 2 - 9 ppm Yellow 10 - 34 ppm Red >35 ppm
	Audible:	>35 ppm increasing frequency w/concentration
Battery:		9V standard alkaline
Ambient Temp:		32° to 104°F (0° to 40°C)

EM151 Specifications

Measurement range	-20" to +20" WG
Accuracy	±1.0% FS
Resolution	0.01" -9.99" to +9.99" WG 0.1" < -10", > +10" WG
Operating range	32° ~ 104°F (0° ~ 40°C), 10 ~ 90% RH non condensing
Battery life	50 hours min with alkaline battery

CD100A Combustible Gas Leak Detector

- **Simple adjustable tic rate**
- **Easy one hand operation**
- **Long 18" gooseneck**
- **Tip light in sensor cover illuminates the area of the leak**
- **Sensor provides accurate detection**
- **Audio and visual tic rate**
- **Headphone jack**
- **One year limited warranty**

C071A Carbon Monoxide Detector

- **Preset alarms**
 - **3-color warning light**
 - **Audible alert**
- **MAX capture**
- **Low battery indicator**
- **CO detection to 999 ppm**
- **Backlit display**
- **One button auto zero**
- **Three year product warranty**
(Five year expected sensor life)

EM151 Electronic Manometer

- **Single input to measure positive and negative pressure to 20" wg**
- **Ruggedized, including rubber boot with integral magnet**
- **Measures in inches water gauge**
- **Auto power-off after 5 minutes of no activity**
- **One year limited warranty**

Distributed By:



1-800-547-5740 • Fax: (503) 643-6322
www.ueitest.com • Email: info@ueitest.com

IN CANADA

Phone: 1-877-475-0648 • Fax: (604) 278-8299
www.ueitest.com • Email: info@ueitest.com

IN EUROPE

Phone: +44 1707 375550 • Fax: +44 1707 393277

